

## PREMIUM SN 0W40

**Premium SN 0W40** is a full synthetic polyalphaolefin (PAO) blend, API SN, super high performance petrol engine oil which combines the latest European specification development in oil formulation and additive technology to provide a lubricating oil with the highest level of protection.

**Premium SN 0W40** reduces oil consumption and exhaust emissions, whilst delivering fuel economical benefits through effective friction reduction and load improvement agents.

Advanced additives and a high viscosity index provide excellent thermal stability, low temperature soot dispersancy and outstanding high temperature deposit control.

It is specifically designed for use in high performance turbo and non turbo petrol engines.

**Premium SN 0W40** can be used in the most advanced European, American and Japanese model cars engines.

**Premium SN 0W40** meets or is recommended for use in the following demanding performance requirements:

API – SN/SM  
ACEA - A3/B4  
MB 229.3, 229.5  
BMW LL-01  
Porsche A40  
VW 502/505  
Renault 0700, 0710

### Benefits

- Formulated for stop – start driving conditions
- Improves engine performance
- Smooth operation for all high performance engines with superior high temperature protection
- Exceeds requirements for petrol and LPG engines
- Extends drain intervals
- Protects engines against rust and corrosion under severe operating conditions

### TYPICAL CHARACTERISTICS

| Properties              | Unit     | Value |
|-------------------------|----------|-------|
| SAE Viscosity Grade     |          | 0W40  |
| Density, kg/lit @ 15 °C |          | 0.85  |
| Viscosity @ 40°C        | cSt      | 71.5  |
| Viscosity @ 100°C       | cSt      | 13.0  |
| Viscosity Index         |          | 185   |
| Flash Point ° C         |          | >220  |
| Pour Point ° C          |          | -40   |
| TBN                     | Mg KOH/g | 7.0   |

### Package Sizes

**1000 litre**  
**205 litre**  
**20 litre**