

## PREMIUM G 5W30

**Premium G 5W30** is a fully synthetic ILSAC GF-5 super high performance engine oil which combines the latest development in oil formulation and additive technology to provide a lubricating oil with the highest level of protection.

**Premium G 5W30** meets General Motors Dexos 1 petrol engine specification requirements.

It reduces oil consumption and exhaust emissions, whilst delivering fuel economical benefits through effective friction reduction and load improvement agents in the latest petrol engines.

Advanced additives and a high viscosity index provide excellent thermal stability, low temperature soot dispersancy and outstanding deposit control.

It is designed for use in high performance turbo and non turbo petrol engines.

**Premium G 5W30** can be used in the most advanced European, American and Japanese model cars, including DOHC or GDi engines. It is not recommended for use in diesel engines.

**Premium G 5W30** meets or is recommended for use in the following requirements:

API – SN/SN RC  
ILSAC GF-5  
DEXOS 1  
Ford WSS-M2C929-A  
Ford WSS-M2C946-A  
Chrysler MS-6395

### Benefits

- Formulated for stop – start driving conditions
- Improves engine performance in turbo and non turbo engines
- Reduces costs with improved fuel efficiency
- Exceeds requirements for petrol and LPG engines
- Wear protection and extended service life
- Protects engines against rust and corrosion under severe operating conditions

### TYPICAL CHARACTERISTICS

| Properties             | Unit     | Value     |
|------------------------|----------|-----------|
| SAE Viscosity Grade    |          | 5W30      |
| Density, kg/lt @ 15 °C |          | 0.875     |
| Viscosity @ 40°C       | cSt      | 55.0      |
| Viscosity @ 100°C      | cSt      | 9.7       |
| Viscosity Index        |          | 160       |
| Flash Point ° C        |          | >210      |
| Pour Point ° C         |          | -40       |
| TBN                    | Mg KOH/g | 7.8       |
| Zinc anti-wear         | ppm      | 830 - 900 |

### Package Sizes

1000 litre  
205 litre  
20 litre  
5 litre