

ATF 3

A Multifunctional Automatic and Powershift Transmission plus Power Steering Fluid for use in cars, trucks, buses and heavy duty machinery requiring a Dexron® III fluid. It provides a reliable friction performance, high temperature stability, superior anti-wear properties, low temperature fluidity and material compatibility required by current specifications.

✓ An automatic transmission fluid specially formulated to conform to GM and Ford specifications.

✓ Supercedes all previous Dexron® IIE, Dexron® IID and Type A Suffix A transmission fluids.

Meets the following performance requirements:

- ATF Dexron® III G/H/M
- Dexron III 6297-M
- Ford MERCON®IV
- Ford M2C185A, M2C-138CJ
- Holden HN 2126 up to 2006
- Power Steering Fluid application
- Allison C-4, TES 389
- Sperry Vickers, Denison and Sundstrand hydraulic pump systems
- Mazda M – III Fluid
- Toyota T Fluid
- Nissan Matic C/D Fluid
- Type A Suffix A
- Audi (up to 1992)
- BMW (up to 2003)
- Fiat (up to 1992)
- Isuzu
- Mercedes Benz 236.1, 236.6, 236.7, 236.9
- Porsche (up to 1992)
- Renault (up to 1997)
- Subaru (up to 2003)
- Volkswagen (up to 1992)
- Volvo 97341 (up to 1997)
- Voith G607, G1363 DIWA
- ZF TE ML 14A

ADVANTAGES

- Improved high temperature characteristics.
- Offers improved gear durability.
- Stable friction properties give improved shift feel on cold start and at operating temperatures.
- Excellent friction, oxidation, thermal and chemical stability due to the superior viscometrics.
- Avoids foaming tendencies in transmissions so that full-bodied lubricant is maintained to all surfaces.
- Improved protection to certain non-ferrous components.
- Improved low temperature characteristics in comparison to Dexron® II, Dexron® IID and Type A Suffix A fluids.
- Improved anti-wear properties.

APPLICATION

- Miscible with all mineral oil and synthetic oil, therefore no flushing is required.

TYPICAL CHARACTERISTICS

Properties	Unit	Value
Specific Gravity		0.853
Viscosity @ 40°C	cSt	35.5
Viscosity @ 100°C	cSt	7.3
Viscosity Index		175
Flashpoint	°C	194
Pour Point	°C	-45

Pack Sizes	1000 litre	205 litre
	20 litre	60 litre
	4 litre	1 litre