

## **PREMIUM V 5W30**

**Premium V 5W30** is a fully synthetic, Polyalphaolefin (PAO) ACEA C3, MID SAPS, ultra high performance petrol and diesel engine oil which combines the latest development in oil formulation and additive technology to provide a lubricating oil with the highest level of protection.

**Premium V 5W30** meets most European diesel engine manufacturers including Mercedes Benz, VW and BMW.

It supports increased oil change intervals, reduces oil consumption and exhaust emissions, whilst delivering fuel economical benefits through effective friction reduction and load improvement agents.

Advanced additives and a high viscosity index provide excellent thermal stability, low temperature soot dispersancy and outstanding high temperature protection.

**Premium V 5W30** can be used in the most advanced European, American and Japanese model car and small vehicle engines.

**Premium V 5W30** is approved or meets the following performance requirements:

API SN/CF  
ACEA - C3  
MB 229.31, 229.51  
BMW LL-04  
Porsche C30  
VW 504.00, 507.00 Approved

### **Benefits**

- Formulated for stop – start driving conditions
- Provides high performance in very long drain intervals
- Protects Diesel Particulate Filters (DPF),
- Protects sensitive exhaust gas treatment systems
- PAO base oil for the highest quality

### **TYPICAL CHARACTERISTICS**

Properties	Unit	Value
SAE Viscosity Grade		5W30
Density, kg/lit @ 15 °C		0.85
Viscosity @ 40°C	cSt	68.0
Viscosity @ 100°C	cSt	12.0
Viscosity Index		170
Flash Point ° C		225
Pour Point ° C		-42
TBN	Mg KOH/g	8.2

### **Package Sizes**

**1000 litre**  
**205 litre**  
**20 litre**  
**5 litre**