

LSA PREMIUM SN 10W30

(Previously EURO 10W30)

A premium quality SAE 10W/30 fuel efficient engine oil designed for the professional workshop and made using the latest synthetic technology base oils. It meets and exceeds that latest API SN/CF and is suitable for most types of petrol and four stroke engines under the most severe and varied operating conditions, such as high temperature motorway driving or low temperature stop-start driving, plus engines with small clearances.

All season, oil for naturally aspirated and turbocharged gasoline and light diesel engines.

- ✓ Improves fuel efficiency.
- ✓ Exceeds modern engine emission control and oil consumption standards.
- ✓ All season high performance SAE 10W/30 engine oil.
- ✓ Excellent for cold crank starting with excellent fluidity characteristics, that provides increased engine life.
- ✓ For normally aspirated and turbo charged gasoline engines.

Meets the following performance requirements:

- SAE Grade 10W/30
- API SN/CF
- ACEA A3, B3, B4
- ILSAC GF-5
- Ford 10W/30 WSS-M2C9-A1
- MB 229.1

APPLICATION

Miscible with all mineral oil and synthetic oil, therefore no flushing is required.

ADVANTAGES

- ✓ Latest SN formulation
- ✓ Fast Flow at cold temperature starting
- ✓ Protection for high temperatures
- ✓ Provides excellent viscometrics: stays in grade and maintains its characteristics even in very severe operations.
- ✓ Protection from piston deposits and maintains engine cleanliness.
- ✓ Improved fuel economy.
- ✓ Suitable for vehicles operating in dusty or sandy conditions, stop-start driving.
- ✓ Suitable for vehicles using LPG and CNG fuel, leaded and unleaded fuel.
- ✓ Compatible with catalytic converters.
- ✓ Excellent protection against wear due to stable lubricating film at full-throttle operation.
- ✓ Protects against sludging.
- ✓ Compatible with all gaskets and seals.
- ✓ Optimum operation of tappets due to the absence of foam.

TYPICAL CHARACTERISTICS

| Properties | Unit | Value |
|--------------------|---------|--------|
| SAE Grade | | 10W/30 |
| Viscosity @ 40°C | cSt | 67.9 |
| Viscosity @ 100°C | cSt | 11.2 |
| Viscosity Index | | 158 |
| Density @ 15°C | g/ml | 0.865 |
| Flash Point COC °C | | 210 |
| Pour Point °C | | -30 |
| TBN | mgKOH/g | 7.2 |

Package sizes

1000 litre
205 litre
20 litre
5 litre
1 litre