ProductData Sheet



DEGREASER

LSA Degreaser is a specially formulated general purpose degreaser. It is a 97% hydrocarbon solvent based degreaser for use in metal degreasing, engine, parts and floor cleaning.

- Colourless to pale yellow liquid.
- Low volatility ensures minimal evaporation losses.
- · Versatile and may be hosed off with water.

PERFORMANCE FEATURES

Solvency – will provide degreasing, emulsifying properties and leave a clean surface.

APPLICATIONS

Maintenance Cleaning – spray or brush on, allow 5 to 10 minutes before hosing off.

Engine & Parts Cleaning – soak parts up to 2 hours, drain then flush with high pressure water, then blow dry.

Floor Cleaning – apply to affected area with mop or stiff broom, rinse off with water and squeegee to dry.

Metal Cleaning – dip or spray to preclean surfaces during manufacturing and prior to electroplating, then rinse off with water after 2 to 5 minutes.

SAFETY – high flash point.

HAZARD CLASSIFICATION

Non Dangerous Goods Irritant Poison Schedule S5 Please consult the MSDS on LSA Degreaser before use.

TYPICAL CHARACTERISTICS

Properties	Unit	Value
Density @ 15°C	g/mL	0.82
Flash Point		>61ºC
Boiling Range	100kPa	150 - 280ºC
Aromatic Content		Mild Odour

Package Sizes

1000 litre 205 litre 20 litre

The information contained herein is accurate at the time of this review. However specifications change from time to time. Ensure specifications meet equipment manufacture requirements.

Lubricant Specialists Australia Unit 2, 1110 Abernethy Road High Wycombe WA 6057 Australia

Tel: +618 6254 7777