

## LSA GREASE ANTI-SEIZE

**Issue Date** February 2016      **Status** Issues by LSA

**Not classified as hazardous according to criteria of NOHSC**

### COMPANY DETAILS

**COMPANY:** Bernadini Pty Ltd (ABN 64 384 013 844) trading as  
Lubricant Specialists Australia

**ADDRESS:** Unit 2, 1110 Abernethy Road  
HIGH WYCOMBE WA 6057

**EMERGENCY TELEPHONE:** 08 6254 7777 (Business)

**TELEPHONE NUMBER:** 08 6254 7777

**FAX NUMBER:** 08 9454 9158

**OTHER INFORMATION:** Visit our website [www.lsa oils.com.au](http://www.lsa oils.com.au)  
Orders 08 6254 7777

### 1. IDENTIFICATION OF MATERIAL

Product Name	LSA GREASE ANTI-SEIZE
Proper Shipping Name	None Allocated
UN Number	None Listed
DG Class	None Allocated
Packing Group	None Allocated
Hazchem Code	None Allocated
Poison Schedule	Not Scheduled
Product Use	Copper and graphite based lubricant designed to minimize seizing of equipment

### 2. HAZARD IDENTIFICATION

**HAZARD CLASSIFICATION:** NON-HAZARDOUS SUBSTANCE  
NON-DANGEROUS GOODS

Hazard classification according to criteria of NOHSC.  
Dangerous goods classification according to Australian Dangerous Goods Code.

**RISK PHRASE (S):**

**IRRITANCY OF PRODUCT:** Not classified as an irritant.

# Material Safety Data Sheet



SENSITISATION OF PRODUCT: Not known to be a sensitiser.

TERATOGENICITY: No teratogenic effects known.

OTHER INFORMATION: Used grease may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and environment on disposal. All used grease should be handled with caution and skin contact avoided as far as possible.

### 3. COMPOSITION – INFORMATION ON INGREDIENTS

CHEMICAL CHARACTERISTICS: Liquid

INGREDIENTS	CAS No.	Proposition
Residual Oils (Petroleum), Solvent De-waxed	64742-62-7	>60 %
Graphite	7782-42-5	10% - 30%
Copper Fines	7440-50-8	10% - 30%
Organic Modified Clay (Organophilic Clay)	68953-58-2	< 10%
1,2,3-Propanetriol (Glycerol Anhydrous)	56-81-5	< 10%
Zinc Diamyldithio carbamate	15337-18-5	< 10%
Tri-Sodium Phosphate Anhydrous	7601-54-9	< 10%

### 4. FIRST AID MEASURES

#### HEALTH EFFECTS

SWALLOWED: If a large quantity is ingested seek immediate medical attention. Give water to drink. DO NOT induce vomiting. If vomiting occurs get immediate medical attention due to aspiration into lungs risk.

EYE: Immediately irrigate with copious amounts of water for at least 15 minutes. Eyelids to be held open. In all cases of eye contamination it is a sensible precaution to seek medical advice.

SKIN: Remove contaminated clothing and wash skin thoroughly with plenty of soap and water. High pressure injection through the skin requires **URGENT** medical attention for possible incision, irrigation and/or debridement. Contact with molten material will require treatment by a physician for burns (Do not remove material).

The information contained herein is accurate at the time of this review. However specifications change from time to time. Ensure specifications meet equipment manufacture requirements.

Review Date 29/2/16 GB  
LSA Grease Anti-Seize

Version: 3

2 of 10

Lubricant Specialists Australia  
Unit 2, 1110 Abernethy Road  
High Wycombe WA 6057  
Australia  
Tel: +618 6254 7777

INHALED:	Remove victim from exposure to fresh air – avoid becoming a casualty. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical advice if effects persist. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have qualified person give oxygen through face mask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage and seek urgent medical aid.
FIRST AID FACILITIES:	Normal washroom facilities are generally suitable. Ensure an eye wash station and safety shower is available and ready for use.
ADVICE TO DOCTOR:	Treat symptomatically.
OTHER INFORMATION:	Keep water and mild soap near work site.

## 5. FIRE FIGHTING MEASURES

### FIRE/EXPLOSION HAZARD

HAZARDS OF USE/STORAGE:	Product is a C2 combustible liquid according to AS 1940. This product is combustible if preheated.
HAZARDS FROM COMBUSTION PRODUCTS:	Combustion products may include: oxides of carbon, aldehydes, incomplete combustion products, smoke, fumes, sulphur oxides, a complex mixture of airborne unidentified organic and inorganic solid and liquid particulates.
FIRE-FIGHTING RECOMMENDATIONS:	If safe to do, remove containers from path of fire. Keep storage tanks, pipelines, containers, fire exposed surfaces, etc. cool with water spray. Avoid spreading liquid and fire by water flooding.
PRECAUTION:	Water stream may cause splattering and spread fire.
SUITABLE EXTINGUISHING MEDIA:	Use foam, carbon dioxide, dry chemical or water spray (fog).

**PROTECTIVE MEASURES:**

Fire fighters should wear self-contained breathing apparatus if risk of exposure to products of combustion.

**REACTIVITY:**

May react with strong oxidizing agents.

## 6. ACCIDENTAL RELEASE MEASURES

**SPILLS & DISPOSAL:**

Slippery when spilt. Avoid accidents, clean up immediately.

**CLEAN-UP PROCEDURE - SMALL SPILLS (20L or less):** Absorb or contain spills with sand, earth or spill control material. Shovel up using non-sparking tools and place in a sound labeled sealable container for subsequent safe disposal. Place leaking containers in a sound labeled drum. Scrub contaminated surfaces with detergent solution. Retain washings as contaminated waste.

**CLEAN-UP PROCEDURES - LARGE SPILLS (Greater than 20L):** Transfer to a sound labeled, sealable container for product recovery or safe disposal. Treat residues as for small spills.

**PERSONAL PRECAUTIONS:** Extinguish naked flames. Remove ignition sources. No smoking. Avoid sparks. Take precautionary measures against static discharges. Avoid contact with skin, eyes and clothing. Evacuate the area of non-essential personnel. Shut off leaks, if possible without personal risk. Do not breathe vapours. Ventilate contaminated area thoroughly. Dispose of according to local regulations.

**OTHER INFORMATION:**

**PROCEDURES IN CASES OF LEAKAGE OR BREAKAGE:** Stop the source of the leak or release and contain spill if possible. Ventilate area. Use respirator and protective clothing outlined in this MSDS. Cover spill with inert absorbent earth. Use a stiff brush to mix thoroughly. Sweep up and place in a sound labeled disposable container. Scrub contaminated area with detergent and water using a stiff brush. Pick up liquid with additional absorbent material and place in a sound labeled disposable container. May require excavation of contaminated soil. Prevent contamination of groundwater or surface water.

## 7. HANDLING AND STORAGE

**PRECAUTIONS FOR SAFE HANDLING:**

When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Prevent spillages. Ensure the appropriate personal protective equipment is used when handling this product. Ensure high

level of personal hygiene is maintained when using this product. That is; always wash hands before eating, drinking smoking or using the toilet.

#### SAFE STORAGE CONDITIONS:

Keep containers closed at all times. Store in a cool place out of direct sunlight. Store away from oxidizing agents. Check containers regularly for leaks. Maximum storage temperature 50°C.

CORROSIVENESS: Not corrosive.

#### STORAGE REGULATIONS:

Store in a well ventilated place away from ignition sources, oxidizing agents, foodstuffs and clothing.  
Keep containers closed when not in use.  
Refer to AS 1940 – The Storage and Handling of Flammable Liquids, and NOHSC: 1015 – National Standard for Storage and Handling of Workplace Dangerous Goods for further information.

## 8. EXPOSURE CONTROLS – PERSONAL PROTECTION

#### NATIONAL EXPOSURE STANDARDS:

No exposure standard has been established for this product. NOHSC Exposure Standard: Oil mists – time weighted average (TWA) 5 mg/m<sup>3</sup> is recommended.

#### OTHER EXPOSURE INFORMATION:

Exposure Standard means the average concentration of a particular substance in the worker's breathing zone, exposure to which, according to current knowledge, should not cause adverse health effects nor cause undue discomfort to nearly all workers. It can be of three forms; time-weighted average (TWA), peak limitation, or short term exposure limit (STEL).

#### ENGINEERING CONTROLS:

Maintain concentration below recommended exposure limit. Special ventilation is not normally required. However, in the operation of certain equipment or at elevated temperatures mists or vapour may be generated and localised exhaust ventilation should be provided to maintain airborne concentration levels below the exposure standard or the Manufacturer's recommended exposure standard.

## RESPIRATORY PROTECTION:

A respirator is not normally required. Airborne concentrations should be kept at lowest level possible. If vapours, mists or dusts are generated and the recommended exposure limit for the product is exceeded, use appropriate AS/NZS 1715/1716 approved half-face filter respirator suitable for organic vapours or air supplied respirator are worn. Air supplied respirators should always be worn when the airborne concentration of the contaminant or the oxygen content of the air is unknown.

**EYE PROTECTION:** Safety glasses, goggles or face shield as appropriate.

**HAND PROTECTION:** Chemical resistant PVC gloves. No protection is required in normal use.

**FOOTWEAR:** Enclosed footwear.

**BODY PROTECTION:** Overalls or similar protective apparel. No skin protection is required in normal use.

**HYGIENE MEASURES:** Always wash hands before eating, drinking, smoking or using the toilet. If contamination occurs, change clothing. Launder contaminated clothing before reuse. Discard internally contaminated gloves.

## SPECIAL PROTECTIVE MEASURES:

The product will not burn unless preheated. Isolate from sources of heat, naked flames or sparks.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

FORM:	Smooth Soft grease
COLOUR:	Copper coloured
ODOUR:	Slight hydrocarbon odour
MELTING POINT:	Not Established
BOILING POINT:	Not Established
DENSITY @ 15°C (kg/L):	0.95 typical
FLASHPOINT, Cleveland Open Cup:	> 200°C

The information contained herein is accurate at the time of this review. However specifications change from time to time. Ensure specifications meet equipment manufacture requirements.



# Material Safety Data Sheet



FLAMMABILITY LIMITS -LOWER:	N/A
FLAMMABILITY LIMITS -UPPER:	N/A
FLAMMABILITY:	Combustible Liquid C2 according to AS 1940.
SOLUBILITY IN ORGANIC SOLVENTS:	Soluble in petroleum solvents.
VAPOUR PRESSURE, mmHg @ 25°C:	< 1 mm
VAPOUR DENSITY (Air = 1):	< 1 mm
VISCOSITY @ 40 °C (mm <sup>2</sup> /s):	Approximately 220
EVAPORATION RATE:	Less than 1 (n-butyl acetate = 1)
AUTO-IGNITION TEMPERATURE:	Not Established
EXPLOSION PROPERTIES:	Not considered an explosion risk under normal conditions of use.
OTHER INFORMATION:	These physical data and other properties do not constitute a specification.

## 10. STABILITY AND REACTIVITY

CHEMICAL STABILITY:	Stable under normal conditions of use.
CONDITIONS TO AVOID:	Excessive heat, open flames or other sources of ignition.
INCOMPATIBLE MATERIALS:	Strong oxidizing agents.
HAZARDOUS REACTIONS:	Does not decompose at ambient temperatures.
HAZARDOUS POLYMERISATION:	Will not occur.

## 11. TOXICOLOGICAL INFORMATION

TOXICOLOGY INFORMATION:	This product contains petroleum base oils, which may be refined by various processes including severe solvent extraction, hydro cracking and hydro treating. These oils have not been listed in the U.S. National Toxicology
-------------------------	--

The information contained herein is accurate at the time of this review. However specifications change from time to time. Ensure specifications meet equipment manufacture requirements.

Program (NTP) Annual Report nor have they been classified by the International Agency for Research on Cancer (IARC) as carcinogenic or probably carcinogenic to humans. Oral LD50 ({}UDO1)} :{} UDO2} mg/kg.

INHALATION:	Inhalation of mists or aerosols can produce respiratory irritation.
INGESTION:	May cause mild irritation of the mouth, throat and stomach with nausea and mild diarrhea. Large amounts can cause vomiting which can lead to aspiration of vomited material into the lungs.
SKIN:	This product is not a primary skin irritant after exposure of short durations. Can have a de-fatting and drying effect of the skin.
EYE:	May cause watering of eyes.
REPRODUCTIVE TOXICITY:	This product contains small amounts of para-dodecylphenol. Rats when given high, repeated daily doses by oral intubation experienced adverse reproductive effects. The relevance of these effects to humans is uncertain.
CHRONIC EFFECTS:	Prolonged or repeated exposure may result in irritation, with the possibility of dermatitis.
MUTAGENICITY:	Mutagenic effects not known.
CARCINOGENICITY:	Product is not a known carcinogen.

## 12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:	<p>Material is not expected to be harmful to aquatic organisms. Leaching and penetration through soils is generally regarded as resulting in long-term persistence.</p> <p>Base oil component – low solubility and float is expected to migrate from water to the land; Expected to partition to sediment and wastewater solids.</p> <p>Do not allow material to enter drains or watercourses.</p>
-------------------------	--

## 13. DISPOSAL CONSIDERATIONS

DISPOSAL CONSIDERATIONS:	Dispose of according to federal, E.P.A. and state regulations.
--------------------------	--



## 14. TRANSPORT INFORMATION

TRANSPORT INFORMATION: Not classified as a Dangerous Good according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

## 15. REGULATORY INFORMATION

POISON SCHEDULE: Not scheduled.

PACKING & LABELLING: No special packaging or labeling requirements.

AUSTRALIAN INVENTORY STATUS: All components are listed or exempted.

## 16. OTHER INFORMATION

LITERATURE REFERENCES:

- \* NOHSC: 2011 National Code of Practice for the preparation of Material Safety Data Sheets.
- \* NOHSC: 1008 Approved Criteria for Classifying Hazardous Substances.
- \* NOHSC: 10005 List of Designated Hazardous Substances.
- \* NOHSC: 1005 Control of Workplace Hazardous Substances, National Code of Practice.
- \* NOHSC: 2007 Control of Workplace Hazardous Substances, National Code of Practice.
- \* NOHSC: 1003 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, National Exposure Standards.
- \* NOHSC: 3008 Exposure Standards for Atmospheric Contaminants in the Occupational Environment, Guidance Note.
- \* NOHSC: 1015 Storage and Handling of Workplace Dangerous Goods, National Standard.
- \* NOHSC: 2017 Storage and Handling of Workplace Dangerous Goods, National Code of Practice.
- \* SUSDP: Standard for the Uniform Scheduling of Drugs and Poisons
- \* ADG: Australian Dangerous Goods Code
- \* MSDS of component materials.

# Material Safety Data Sheet



## 17. CONTACT POINT

Contact

Tel: 08 6254 7777

Fax: 08 9454 9158

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Material Safety Data Sheets are updated frequently. Please ensure you have a current copy.

User Information Issue Date:

29/2/16

Supersedes Issue Date: 3/6/11

Reason(s) for issue

MSDS Update

Safety data sheets are updated frequently. Please ensure that you have a current copy.

N\A = Not allocated.

**END MSDS**

The information contained herein is accurate at the time of this review. However specifications change from time to time. Ensure specifications meet equipment manufacture requirements.

Review Date 29/2/16 GB  
LSA Grease Anti-Seize

Version: 3

10 of 10

Lubricant Specialists Australia  
Unit 2, 1110 Abernethy Road  
High Wycombe WA 6057  
Australia  
Tel: +618 6254 7777