

FOUR STROKE 30

A high performance monograde engine oil for Four Stroke Lawn Mower engines, plus petrol and diesel Stationary engines, requiring an SAE 30 grade oil.

Recommended for four stroke petrol lawn mower engines running on leaded, unleaded and lead replacement petrol, especially Briggs and Stratton engines.

Not suitable for two stroke petrol and diesel engines.

A monograde engine oil designed to meet the requirements of manufacturers calling for an SAE 30 grade oil.

Meets the following performance requirements:

- SAE Grade 30
- API SG/SF/CD
- ACEA E2
- CCMC D2
- BRIGGS & STRATTON SE/SF SAE 30

ADVANTAGES

- Maintains engine cleanliness leading to longer engine life.
- Protects against rust, corrosion, wear and sludging.
- Prevents rings sticking.
- Reduces piston deposits.
- Compatible with all gaskets and seals.

APPLICATION

- Miscible with all mineral oil and synthetic oil, therefore no flushing is required

TYPICAL CHARACTERISTICS

Properties	Unit	Value
SAE Grade		30
Viscosity@ 40°C	cSt	107
Viscosity@ 100°C	cSt	12.0
Viscosity Index		94
Density @ 15°C	g/mL	0.89
Flash Point °C		240
Sulphated Ash content	%	1.0

Pack Sizes

205 litre
20 litre
4 litre
1 litre