

LSA GREASE NON-MELT MOLY 2

THICKENER	NLGI	TEMP RANGE	BASE OIL VISCOSITY	SOLID LUBRICANT CONTENT	WATER RESISTANCE ON A SCALE OF 3
BENTONITE	2	0° C to +200° C	145 cSt @ 40° C	YES	3

Grease Non-Melt Moly 2 is a premium, extreme pressure, multi-purpose, long life with solid lubricants molybdenum disulphide and graphite. The bentonite thickener is non-melt, inorganic clay providing better protection at high temperatures compared with soap greases.

FEATURES

- Non-Melt high temperature grease
- Excellent extreme pressure properties
- Very good oxidation and rust protection
- Outstanding high temperature properties
- Good water resistance

APPLICATION

Grease Non-Melt Moly 2 is recommended for slow and medium speed bearings in kiln equipment, steam valves, door hinges, hot conveyor bearings and many industrial and construction applications.

BENEFITS

- Does not melt at high temperatures
- Provides effective lubrication for bearings, ball joints and driveshafts
- Does not washout under water ingress conditions
- Stays in place in extreme environments

TYPICAL CHARACTERISTICS

TEST	METHOD	VALUE
COLOUR	VISUAL	GREY/ BLACK
WORKED PENETRATION	ASTM D 217	265 - 295
DROP POINT, MINIMUM	ASTM D 2265	NON-MELT

Package Sizes

16.9kg Pail