

## LSA GREASE LXR 2

| THICKENER          | NLGI | TEMP RANGE       | BASE OIL VISCOSITY | TACKINESS<br>ADDITIVE | EP  | WATER<br>RESISTANCE<br>ON A SCALE OF<br>3 | SOLID LUBRICANT |
|--------------------|------|------------------|--------------------|-----------------------|-----|---|-----------------|
| LITHIUM<br>COMPLEX | 2    | -20° C to 150° C | 680 cSt @ 40° C    | YES                   | YES | 2   | NO              |

**GREASE LXR 2** is a premium heavy-duty grease for plain bearings operating under high load and high temperatures in mining, quarries and similar industries. Preferred for off-road parts such as ball joints and drive shafts.

**GREASE LXR 2** is fortified with extreme pressure anti wear and anti-corrosion additives and compounded with tackiness agent to provide excellent sealing against ingress of dirt and moisture.

### BENEFITS

- Excellent load bearing, See four-ball weld below.
- Compatible with other lithium and lithium complex greases.
- Very high viscosity base oil for high film strength.
- Corrosion resistance for wet conditions.
- Excellent mechanical stability under vibrating conditions.

### TYPICAL CHARACTERISTICS

| TEST               | VALUE           |
|--------------------|-----------------|
| COLOUR             | DARK RED        |
| SOAP TYPE          | LITHIUM COMPLEX |
| WORKED PENETRATION | 280             |
| DROP POINT         | 280° C          |
| FOUR BALL WELD, KG | 400 KG          |

**Package Sizes**      **180 kg**    **20 kg**    **450 gm**