SAFETY DATA SHEET



Revision Date 12/01/2022

Version 5

HAZARDOUS SUBSTANCE - NON-DANGEROUS GOODS

HAZARDOUS SUBSTANCE - NON-DANGEROUS GOODS			
	substance / mixture and of the company / undertaking		
Product identifier			
Product name	LSA GREASE LXMO2		
Product code	1600-02-0000		
SDS no.	1600-02-0000		
Product type	Liquid.		
Relevant identified uses of the substance or mixtu	ure and uses advised against		
Use of the substance/mixture	LUBRICANT		
	For specific application advice see appropriate Technical Data Sheet or consult our company representative.		
Details of the supplier of the safety data sheet			
Supplier	Bernadini Pty Ltd		
	Trading as LUBRICANT SPECIALISTS AUSTRALIA (LSA)		
	Unit 2, 1110 Abernethy Road		
	High Wycombe WA 6057		
	Telephone +61 8 6254 7777		
	Fax +61 8 9454 9158		
E-mail address	perth@lsaoils.com.au		
Emergency telephone number	+61 8 6254 7777		
SECTION 2: Hazards identification	n		
Classification of the substance or mixture			
GHS classification	Mixture		
CLASSIFIED AS HAZARDOUS SUBSTAN	ICE, NON-DANGEROUS GOODS. ACCORDING TO AUSTRALIAN WHS REGULATIONS AND ADG CODE Hazard Category 2A		
Other hazards			
Other hazards which do not result in	Skin irritation. Harmful to aquatic life with long lasting effects.		
classification	Used oil may contain hazardous components which have the potential to cause skin cancer.		
	See Toxicological Information, section 11 of this Safety Data Sheet.		
Label elements			
Hazard pictograms			
Signal word	Warning		
Hazard statements	H319: Causes serious eye irritation.		
Precautionary statements			
Prevention	P264: Wash face, hands and any exposed skin thoroughly after handling.		
	P280: Wear eye protection/face protection.		
Response	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
	P337+313: If eye irriatation persists: get medical advice/attention		
Storage	Not applicable.		
Disposal	Not applicable.		
Supplemental label elements	Safety data sheet available on request.		
Special packaging requirements			
Containers to be fitted with child-resistant	Not applicable.		
fastenings			

SECTION 3: Composition/information on ingredients

Substance / mixture

Mixture

Product / ingredient name	%	CAS Number	Hazard Classification	Risk Phrase/Hazard Statements
Distillates (petroleum), hydrotreated heavy naphthenic	40 - 70%	64742-52-5	Aspiration Toxicity Cat. 1	H304, P301+310, P331, P405
Distillates (petroleum), hydrotreated heavy paraffinic	20 - 40%	64742-54-7	Not classified	Not applicable
Antimony, tris (diphenylcarbamodithioato-S,S') - (OC-6- 11)	< 3%	15890-25-2	Not classified	Not applicable
Molybdenum (IV) Sulfide	< 5%	1317-33-5	Not classified	Not applicable
Graphite	< 3%	7782-42-5	Not classified	Not applicable
Boron lithium oxide (B4Li2O7)	< 5%	12007-60-2	Not classified	Not applicable
Zinc Dialkyldithiophosphate	< 2%	-	Not classified	Not applicable

*The exact percentage of ingredients is confidential.

Occupational exposure limits, if available, are listed in Section 8

escription of first aid measures	
Eye contact	In case of contact with eyes, immediately flush eyes with plenty of water for at least 15 minutes. Keep eye w open while rinsing.Remove any contact lenses. Seek medical advice.
Skin contact	Wash off with soap and plenty water or use recognised skin cleanser. Take off contaminated clothing and she immediately. Get medical attention if irritation develops. If product is injected into or under the skin due to reason, the victim, regradless of size or appearance of wound, should seek immediate medical attention.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms appear.
Ingestion	Drink plenty of water. In general no treatment is necessary unless large quantities are swallowed. Do not indu vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur or contact Poison Information Centre on 13 11 26 (Australia Wide).
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

See Section 11 for more detailed information on health effects and symptoms.

Indication of any immediate medical attention and special treatment needed notes to physician

Treatment should in general be symptomatic and directed to relieving any effects.

SECTION 5: Fire fighting measu	res		
Extinguishing media			
Suitable extinguishing media	In case of fire, use water spray (fog), foam, dry chemical, carbon dioxide extinguisher or sand to extinguish flames.		
Unsuitable extinguishing media	Do not use water jet.		
Special hazards arising from the substance or m	nixture		
Hazards from the substance or mixture	In a fire or if heated, a pressure increase will occur and the container may burst.		
Hazardous combustion products	Combustion products may include the following:		
	Airborne solid and liquid particles, gases (smoke), carbon oxides (CO, CO2) (carbon monoxide, carbon dioxide) unidentifies inorganic and organic compounds.		
Advice for firefighters			
Special precautions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shal be taken involving any personal risk or without suitable training.		
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.		

SECTION 6: Accidental release	measures
Personal precautions, protective equipment an	nd emergency procedures
For non-emergency personal	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency personnel".
Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containment and clo	eaning up
Small Spill	Stop leak if without risk. Move containers from spill area. Shovel into an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large Spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and shovel/place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
Reference to other sections	
	See Section 1 for emergency contact information.
	See Section 5 for firefighting measures.
	See Section 8 for information on appropriate personal protective equipment.
	See Section 12 for environmental precautions.
	See Section 13 for additional waste treatment information.
SECTION 7: Handling and store	240

SECTION 7: Handling and storage	ge
Precautions for safe handling	
Protective measures	Put on appropriate personal protective equipment.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/ containers designed for use with this product. Do not store in unlabelled containers. Keep away from other oxidizing and incompatible materials.
Not suitable	Prolonged exposure to elevated temperature. High temperature may create pressure buildup inside container and chances of container busting or leaking may occur under aggravated conditions.
Specific end use(s) Recommendations	See section 1.2 and Exposure scenarios in annex, if applicable.

SECTION 8: Exposure controls / personal protection

Control parameters

Occupational exposure limits

Product / ingredient name

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy paraffinic	ACGIH TLV (United States).
	TWA: 5 mg/m ³ 8 hours. Issued/Revised:
	11/2009 Form: Inhalable fraction

Antimony, tris (diphenylcarbamo	dithioato-S.S') - (OC-6-11)	ACGIH TLV (United States).		
fataneny, ale (apronycenearie		TWA: 0.5 mg/m ³ sb 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction		
Molybdenum (IV) Sulfide		ACGIH TLV (United States). TWA: 10 mg/m ³ Mo inhalable fraction. TWA: 3 mg/m ³ respirable fraction		
Graphi	ie	-		
Boron lithium oxide (B4Li2O7)		ACGIH TLV (United States). STEL: 6 mg/m ³ inhalable fraction. TWA: 2 mg/m ³ Inhalable fraction		
Recommended monitoring procedures	may be required to determine the e use respiratory protective equipmen	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitori may be required to determine the effectiveness of the ventilation or other control measures and/or the necesity use respiratory protective equipment. Reference should be made to apropriate monitoring standards. Reference national guidance documents for methods for the determination of hazardous substances wil also be required.		
Recommended monitoring procedures	may be required to determine the ef- use respiratory protective equipmer European Standard EN 689 (Workp chemical agents for comparison w (Workplace atmospheres - Guide fi chemical and biological agents) European the performance of procedures for	with exposure limits, personal, workplace atmosphere or biological monitoring frectiveness of the ventilation or other control measures and/or the necessity to it. Reference should be made to monitoring standards, such as the following lace atmospheres - Guidance for the assessment of exposure by inhalation to <i>i</i> th limit values and measurement strategy) European Standard EN 1404; or the application and use of procedures for the assessment of exposure to ropean Standard EN 482 (Workplace atmospheres - General requirements for or the measurement of chemical agents) Reference to national guidance mination of hazardous substances will also be required.		
Derived No Effect Level Predicted No Effect Concentration	No DNELs / DMELs available. No PNECs available			
Exposure controls				
Appropriate engineering controls	Provide exhaust ventilation or other respective occupational exposure lin	engineering controls to keep the relevant airborne concentrations below the nits.		
	controlled. Personal protective equi engineering controls) have been su	build be assessed for their risks to health, to ensure exposures are adequated pment should only be considered after other forms of control measures (e.g itably evaluated. Personal protective equipment should conform to appropriat opt in good condition and properly maintained.		
	standards. For further information of	ve equipment should be consulted for advice on selection and appropriat contact your national organisation for standards. The final choice of protective assessment. It is important to ensure that all items of personal protective		
Environmental exposure controls	requirements of environmental pr	k proces equipment should be checked to ensure. they comply with th otection legislation. In some cases, fume scrubers, filters or enginerin ent wil be necessary to reduce emissions to acceptable levels.		
Individual protection measures				
Hygiene measures		roughly after handling chemical products, before eating, smoking and using th ing period. Ensure that eyewash stations and safety showers are close to th		
Respiratory protection	depends upon the chemicals being equipment. Safety procedures sh	ear suitable respiratory equipment. The correct choice of respiratory protectio handled, the conditions of work and use, and the condition of the respirator ould be developed for each intended application. Respiratory protectio en in consultation with the supplier /manufacturer and with a ful assessment of		
Respiratory protection	Respiratory protective equipment i ventilation to control exposure.	is not normally required where there is adequate natural or local exhaus		
	In case of insufficient ventilation, we	ar suitable respiratory equipment.		

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Safety glasses with side shields.

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove wil break down after repeated chemical exposures). Most gloves provide only a short ime of protection before they must be discarded and replaced. Because specifc work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the suplier/manufacturer and with a ful assessment of the working conditions.

Hand protection

Eye / face protection

Skin protection Hand protection

General Information:

Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).

Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.

Recommended: Nitrile gloves.

Breakthrough time:

Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:

Continuous contact:

Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained. If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.

Short-term / splash protection:

Recommended breakthrough times as above.

It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.

Glove Thickness:

For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.

Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:

	 Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
	• Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.
Skin and body	Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties Information on basic physical and chemical properties

Appearance	
Physical state	Semi-solid
Colour (ASTM D1500)	Black
Odour	Slight hydrocarbon
Odour threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point (ASTM D97), (°C)	Not available.
Flash point (ASTM D92), (°C)	260
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	< 0.13 kPa (< 1 mm Hg)
Vapour density (air = 1)	< 1
Relative density	Not available.
Density (ASTM D4052) @15°C, (g/cm3)	0.87
Solubility(ies)	Not soluble in water.
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Kinematic Viscosity (ASTM D445) @40°C, (cSt)	220
Kinematic Viscosity (ASTM D445) @100°C, (cSt)	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

Other information

Electrical conductivity: Though no data available, this material is not expected to be a static accumulator.

SECTION 10: Stability and reactivity		
Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.	
Chemical stability	The product is stable.	
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.	
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).	

Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Information on toxicological effects	rmation Mixture			
Acute toxicity estimates	25.49% of the mixture consists of ingredients of unknown toxicity. The values are calculated based on section 3.1 of GHS document.			
Ingredient	Oral Toxicity (LD50)	Dermal Toxicity (LD50)	Inhalation Toxicity (LC50)	
Mixture	10188 mg/kg, accute toxicity estimate	-	-	
Information on the likely routes of exposure	Routes of entry anticipated:	Dermal, Inhalation.	<u> </u>	
Potential acute health effects				
Inhalation	Vapour inhalation under am	bient conditions is not normally a p	roblem due to low vapour pressure.	
Ingestion	No known significant effects	s or critical hazards.		
Skin contact	Defatting to the skin. May c	ause skin dryness and irritation.		
Eye contact	Causes serious eye irritation.			
Symptoms related to the physical, chemical and	toxicological characteristics			
Inhalation	No specific data.			
Ingestion	No specific data.			
Skin contact	Adverse symptoms may inc irritation dryness cracking	lude the following:		
Eye contact	No specific data.			
Delayed and immediate effects and also chronic		mexnosure		
Inhalation			may cause irritation of the respiratory tract.	
Ingestion Skin contact Eye contact	Ingestion of large quantities may cause nausea and diarrhoea.			
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.			
Eye contact	Potential risk of transient sti	nging or redness if accidental eye o	contact occurs.	
Potential chronic health effects				
General	USED LUBRICANTS Used lubricants may contain hazardous components which have the potential to cause skin cancer. Frequent of prolonged contact with all types and makes of used lubricants must therefore be avoided and a high standard of personal hygiene maintained.			
Sensitization	No known significant effects	s or critical hazards.		
Carcinogenicity	No known significant effects			
Mutagenicity	No known significant effects			
Developmental effects	No known significant effects			
Fertility effects	No known significant effects			
STOT - single exposure	No known significant effects			
STOT - repeated exposure	No known significant effects			
Aspiration Hazard	No known significant effects			

SECTION 12: Ecological information			
Toxicity			
Environmental hazards	Not classified as dangerous		
	Based on data available for this or related materials.		
Environmental hazards	The environmental impact of this product has not been fully investigated.		
Persistence and degradability	No information available		
Bioaccumulative potential	No information available		

96hr LC50 (for fish), mg/l	>5000		
48hr EC50 (for crustacean), mg/l	>1000		
Mobility in soil			
Soil / water partition coefficient (KOC)	Not available.		
Mobility	Spillages may penetrate the soil causing ground water contamination.		
Results of PBT and vPvB assessment			
PBT	Not applicable.		
vPvB	Not applicable.		
Other adverse effects			
Other ecological information	No information available		

SECTION 13: Disposal considerations Disposal methods The generation of waste should be avoided or minimised wherever posible. Signifcant quanties of waste product residues should not be disposed of via the foul sewer but procesed in a suitable efluent reatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at al times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfil should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and run off and contact with soil, waterways, drains and sewers. 13.1 Waste treatment methods Product Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person / licensed waste disposal contractor in accordance with local regulations. Hazardous waste No Packaging Methods of disposal Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations. **Special precautions** This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

Land (as per ADG classification)	Not regulated
This material is not classified as dangero	ous under ADG Code.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is not classified as dangerous under IATA regulations.

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	Not regulated.	Not regulated.	Not regulated.
Transport hazard class(es)	Not regulated.	Not regulated.	Not regulated.
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	No.	No.	No.
Special precautions for user	-	-	-

Special precautions for user

Not available.

4 -

SECTION 15: Regulatory infor	mation
	/legislation specific for the substance or mixture
Substances of very high concern	
None of the components are listed.	
Safety, health and environmental regulations	specific for the product
	No known specifc national and/or regional regulations aplicable to this product (including its ingredients).
Poison schedule	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
Classifications	Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling Chemicals.
	The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].
Hazard codes	Accute and Chronic Health Hazard.
Risk phrases	None allocated
Safety phrases	Non allocated
Inventory listing(s)	All components are listed on ACIS, or are exempt.
Regulation acording to other foreign laws	
REACH Status	For the REACH status of this product please consult your company contact, as identifed in Section 1.
United States inventory (TSCA 8b)	All components are listed or exempted.
Australia inventory (AICS)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	At least one component is not listed.
Japan inventory (ENCS)	All components are listed or exempted.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	All components are listed or exempted.

This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16. Other information

Chemical Safety Assessment

Abbreviations and acronyms	ACGIH = American Conference of Government Industrial Hygenists
	ADG = Australian Dangerous Goods Code
	ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
	ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
	AICS = Australian Inventory of Chemical Substances
	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	CAS = Chemical Abstracts Service
	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] CSA = Chemic Safety Assessment
	CSR = Chemical Safety Report
	DMEL = Derived Minimal Effect Level
	DNEL = Derived No Effect Level
	DPD = Dangerous Preparations Directive [1999/45/EC]
	DSD = Dangerous Substances Directive [67/548/EEC]
	EINECS = European Inventory of Existing Commercial chemical Substances ES = Exposure Scenario
	EMS = Emergency Schedules (Emergency Procedure for Ships Carrying Dangerous Goods)
	ENCS = Existing and New Chemical Substances
	EUH statement = CLP-specific Hazard statement
	EWC = European Waste Catalogue
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	IARC = International Agency for Research on Cancer
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LC50 = Lethal Concentration, 50% / Medium Lethal Concentration
	LD50 = Lethal Dose, 50% / Medium Lethal Dose
	Log Pow = logarithm of the octanol/water partition coefficient
	MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by t Protocol of 1978. ("Marpol" = marine pollution)
	· · · · · · · · · · · · · · · · · · ·

	OECD = Organisation for Economic Co-operation and Development			
	OEL = Occupational Exposure Limits			
	PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration			
	RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = Registration Number			
	SAA/SNZ HB76 = Dangerous Goods Initial Emergency Response Guide			
	SADT = Self-Accelerating Decomposition Temperature			
	STEL = Short-Term Exposure Limit			
	STOT-RE = Specific Target Organ Toxicity - Repeated Exposure			
	STOT-SE = Specific Target Organ Toxicity - Single Exposure			
	SUSMP = Standard for the Uniform Scheduling opf Medicines and Poisons			
	SVHC = Substances of Very High Concern			
	SWA = Safe Work Australia			
	TLV = Threshold Limit Value			
	TSCA = Toxic Substance Control Act			
	TWA = Time weighted average			
	UN = United Nations			
	UVCB = Complex hydrocarbon substance			
	VOC = Volatile Organic Compound			
	vPvB = Very Persistent and Very Bioaccumulative			
	WHS = Work Health and Safety Regulations			
History				
History	10/100/0000			
Date of issue / Date of revision	12/Jan/2022	000		
Date of previous issue	10-Jan-2021	SDS		
Prepared by	Bernadini Pty Ltd trading as Lubricant Specialists Australia (LSA)			

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from LSA.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. LSA shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact LSA to ensure that this document is the most current available. Alteration of this document is strictly prohibited.