Lubricant Specialists Australia

PRODUCT DATA SHEET

P: +61 8 6254 7777
Unit 2, 1110 Abernethy Road,
High Wycombe, WA 6057
ABN: 64 384 013 844

ATF III

ATF III is a multifunctional automatic and powershift transmission plus power steering fluid for use in cars, trucks, buses, and heavy-duty machinery requiring a DX3 fluid. It provides a reliable friction performance, high temperature stability, superior anti-wear properties, low temperature fluidity and material compatibility required by current specifications pre-2005.

Meets the following specifications:

- Alison C4, TES 389
- ATD DX3 G/H
- Ford MERCON
- Ford M2C-138CJ
- GM: IIIH, IIIG, IID
- Mazda M-III
- MB: 236.2
- Voith: 55.6335
- Volvo: 97325, 97335, 97340
- ZF TE ML 05L.09L, 21L

Typical Characteristics:

Properties	Method	Unit	Value
Colour			Red
Viscosity @ 40°C	ASTM D445	cSt	35.5
Viscosity @ 100°C	ASTM D445	cSt	7.3
Viscosity Index	ASTM D2770		177
Density @ 15°C	ASTM D4502	g/ml	0.853
Flash Point	ASTM D92	°C	194
Pour Point	ASTM D97	°C	-45

Package Sizes:

- 1000L
- 200L
- 20L
- 5L
- 1L

The information contained herein is accurate at the time of this review.
However, specifications may change over time.