

ATF Multitrans LV

ATF Multitrans LV is an advanced synthetic automatic transmission fluid engineered for maximum fuel efficiency and precision shift performance. It covers a wide range of automatic transmissions calling for the latest generation ATF fluid technology.

Typical Characteristics:

Properties	Method	Unit	Value
Colour			Red
Viscosity @ 40°C	ASTM D445	cSt	29.7
Viscosity @ 100°C	ASTM D445	cSt	6.1
Viscosity Index	ASTM D2770		160
Density @ 15°C	ASTM D4502	g/ml	0.848
Flash Point	ASTM D92	°C	200
Pour Point	ASTM D97	°C	-45

Package Sizes:

- 1000L
- 200L
- 20L
- 5L

Meets the following specifications:

- Aisin Warner AW 1
- Audi, VW G 055 005, G 055 162, G 052 540
- BMW 83220142516/83222152426
- Chrysler 68171866AA
- Ford Mercon LV, Mercon SP, NGF
- M2C919D, M1375.4
- Mercon ULV (SFU)
- General Motors Dexron VI
- Dexron ULV (SFU)
- Honda DW-1
- Hyundai, Kia SP/SPH-IV/SPH-IV RR
- NWS 9638 T5
- JASO 1-A-LV
- JWS 3324
- Land Rover TYK500050
- Mazda FZ
- Mercedes Benz 236.12/.14/.15/.16/.17/.41
- Mitsubishi SP-IV, ATF J3, PA, ATF-MA1
- Nissan Matic S, Matic W
- Porsche P/N 043 304 00
- Saab 93 165 147
- Toyota, Lexus WS (JWS 3324)
- Volvo 6-speed 31256774/31256675
- ZF 6-speed Transmissions