

Hydraulic HVI 32

Hydraulic HVI 32 is a high viscosity index, high thermal stability, low pour points premium hydraulic fluid, developed for use in all types of hydraulic equipment operating in a wide range of temperature conditions.

This product is designed with highly refined lubricating base oils and zinc anti-wear additives for automotive and industrial hydraulic systems, transmissions, and pumps.

They also inhibit foam from forming in the oil and offer protection against rust and corrosion in the event of water contamination.

Meets the following specifications:

- AFNOR NFE 48-691
- ASTM D2619 HF-0
- Denison HF-0, 1, 2
- Cincinnati Machine
- Denison HF-0, 1, 2
- DIN 51524 PART 1,2,3 (HVPL)
- Eaton Brochure 03-401-2010
- Parker Denison HF-0
- Parker Hannifin France HF-0 Approved
- Sperry Vickers 1-286-S, M-2950-S
- US Steel 126, 127

Typical Characteristics:

Properties	Unit	Value
ISO Grade		32
Viscosity @ 40°C	cSt	32
Viscosity @ 100°C	cSt	6.2
Viscosity Index		145
Density @ 15°C	g/ml	0.86
Flash Point	°C	210
Pour Point	°C	-30

Package Sizes:

- 1000L
- 200L
- 20L



PHOENIX®



SYNFORCE
LUBRICANTS