

## White Oil FG 15

**White Oil FG 15** is a high-purity paraffinic mineral oil that meets the standards of the US Pharmacopoeia (USP) and British Pharmacopoeia (BP). It complies with the US FDA Regulation CFR 172.878, making it suitable for use in non-food articles that encounter food.

This oil is NSF 3H registered and is recommended for various applications, including pharmaceutical manufacturing, cosmetic preparations, food processing, and packaging operations. It is also used in general processes requiring low sulphur content and as a lubricant for sewing, knitting, and cloth cutting machines.

**White Oil FG 15** offers several benefits, such as compliance with major national pharmacopoeia requirements, high purity standards for medicinal and cosmetic applications, and oxidation stability to resist gum and sludge deposits. It provides good lubricity, protecting against wear, and has a good shelf life.

### Meets the following specifications:

- ISO 15

### Typical Characteristics:

Properties	Method	Unit	Value
ISO Grade			15
Viscosity @ 40°C	ASTM D445	cSt	15
Density @ 15°C	ASTM D4502	g/ml	0.82 to 0.84
Flash Point	ASTM D92	°C	>160
Pour Point	ASTM D97	°C	<-15

### Package Sizes:

- 1000L
- 20L



**PHOENIX®**



**SYNFORCE**