P: +61 8 6254 7777
Unit 2, 1110 Abernethy Road,
High Wycombe, WA 6057
ABN: 64 384 013 844

Hydraulic AW 32

Hydraulic AW 32 is designed with highly refined lubricating base oils and zinc anti-wear additives, and low pour points, for automotive and industrial hydraulic systems which operate at moderate temperatures.

Meets the following specifications:

- ISO 32
- AFNOR NF E 48-603 (HL)
- Cincinnati Machine
- Denison HF-0
- DIN 51524 PART 1 & 2
- Eaton Brochure 03-401-2010
- Fives Cincinnati P-68
- Fives Cincinnati P-69
- Fives Cincinnati P-70
- Parker Denison HF-0
- Parker Hannifin France HF-0 Approved
- Sperry Vickers 1-286-S, M-2950-S
- US Steel 126, 127

Typical Characteristics:

Properties	Method	Unit	Value
ISO Grade	ASTM D2422		32
Viscosity @ 40°C	ASTM D445	cSt	32
Viscosity @ 100°C	ASTM D445	cSt	5.4
Viscosity Index	ASTM D2770		103
Density @ 15°C	ASTM D4502	g/ml	0.87
Flash Point	ASTM D92	°C	215
Pour Point	ASTM D97	°C	-33

Package Sizes:

- 1000L
- 200L
- 20L

The information contained herein is accurate at the time of this review. However, specifications may change over time.