

## **PX Eco Lite FE2 5W30**

**PX Eco Lite FE2 5W30** is a premium, full synthetic lubricant formulated with advanced mid SAPS HYBRID+ additive technology, tailored for modern petrol and petrol/electric hybrid engines. Licensed to meet API SP Resource Conserving and ILSAC GF-6A specifications, it offers exceptional protection against cold starts, frequent stop/start driving, fuel dilution, and water condensation. **PX Euro Lite FE 5W30** enhances engine durability, improves fuel economy, and reduces turbocharger deposits, making it ideal for vehicles requiring SAE 5W-30 oils.

Compatible with a wide range of manufacturers—including GM, Ford, Chrysler, Toyota, Honda, and more—**PX Euro Lite FE 5W30** supports flex-fuel systems and ethanol blends up to E85, as well as dedicated LPG systems. It delivers excellent resistance to viscosity breakdown, enhanced LSPI protection, and extended oil drain intervals. Optimized for hybrid applications, this oil is catalyst and oxygen sensor friendly, ensuring cleaner engine performance and longer engine life.

### **Meets the following specifications:**

- API SP
- Chrysler MS-6395
- DX1G2
- Ford WSS-M2C963-A, WSS-M2C962-A
- ILSAC GF-6A
- SAE 5W-30

### **Advantages & Benefits:**

- Superior engine protection - Minimizes wear, sludge, and deposits for longer engine life and cleaner operation
- Hybrid-ready performance - Optimized for stop/start driving and cold starts in petrol/electric hybrid vehicles
- Fuel efficiency - Meets ILSAC GF-6A standards for improved fuel economy and long-term fuel retention
- Advanced protection - Guards against LSPI and reduces turbocharger deposits in modern engines
- Wide compatibility - Suitable for vehicles running on petrol, LPG, and ethanol blends up to E85



**Typical Characteristics:**

Properties	Method	Unit	Value
SAE Grade	SAE J 300		5W-30
Viscosity @ 40°C	ASTM D445	cSt	60
Viscosity @ 100°C	ASTM D445	cSt	10
Viscosity Index	ASTM D2770		170
Density @ 15°C	ASTM D4502	g/ml	0.87
Flash Point	ASTM D92	°C	215
Pour Point	ASTM D97	°C	-38
TBN	ASTM D2896	Mg KOH/g	7

**Package Sizes:**

- 1000L
- 200L
- 20L