

PX Euro 5W30

PX Euro 5W30 is a high-performance full synthetic engine oil engineered to meet the demands of modern automotive technology. Designed for use in petrol, diesel, and hybrid vehicles, it delivers exceptional protection and performance under high-pressure conditions, helping to reduce friction and maintain engine efficiency across a wide range of operating environments.

This oil is suitable for vehicles equipped with advanced emission systems, including those with diesel particulate filters, and supports extended drain intervals without compromising protection. **PX Euro 5W30** is trusted by leading global manufacturers such as Volkswagen, BMW, Mercedes-Benz, and Porsche, making it an ideal choice for drivers seeking reliable performance and durability. Whether navigating city traffic or long-distance driving, it ensures consistent engine protection and responsiveness when it matters most.

Meets the following specifications:

- ACEA C3
- API SP
- BMW LL-04
- MB 229.31, 229.51/52
- OPEL OV0401547
- Porsche C30
- SAE 5W-30
- VW 504.00/507.00

Advantages & Benefits:

- **Wide Compatibility:** Suitable for petrol, diesel, and hybrid engines, including those with advanced emission systems.
- **Improved Efficiency:** Helps reduce friction under pressure, supporting better fuel economy and engine responsiveness.
- **Reliable Protection:** Maintains performance across varied temperatures and driving conditions.
- **Proven Performance:** Developed to meet the high standards of leading global automotive manufacturers.

Typical Characteristics:

| Properties | Method | Unit | Value |
|-------------------|------------|----------|-------|
| SAE Grade | SAE J 300 | | 5W-30 |
| Viscosity @ 40°C | ASTM D445 | cSt | 68 |
| Viscosity @ 100°C | ASTM D445 | cSt | 12 |
| Viscosity Index | ASTM D2770 | | 170 |
| Density @ 15°C | ASTM D4502 | g/ml | 0.85 |
| Flash Point | ASTM D92 | °C | 220 |
| Pour Point | ASTM D97 | °C | -38 |
| TBN | ASTM D2896 | Mg KOH/g | 8.2 |

Package Sizes:

- 1000L
- 200L
- 20L