

Multitranz ATF 3H

PX Multitranz ATF 3H is a premium synthetic automatic transmission fluid (ATF) designed to meet the performance requirements of DX II, DX III, and Mercon specifications. Engineered for use in a wide range of passenger and light commercial vehicles manufactured prior to the mid-2000s, it is suitable for automatic transmissions and power steering systems where older-generation ATFs are specified. Formulated to the last-generation DX IIIH standard, it delivers enhanced thermal stability, smoother gear shifts, and extended service life under demanding operating conditions.

Dyed red for easy leak detection, **PX Multitranz ATF 3H** is fully compatible with earlier DX and Mercon-type fluids, making it ideal for both top-ups and complete fluid replacement. Its advanced synthetic formulation offers excellent low-temperature fluidity, increased clutch pack capacity, and superior protection for copper and bronze components.

This ATF is also suitable for hydraulic systems where ISO 22/32 or SAE 10W oils are recommended. It is not recommended for CVT, DCT, or systems requiring DX VI, Mercon V, SP, or LV fluids

Advantages & Benefits:

- Enhanced Gear Shift Performance: Provides smoother and more durable gear changes, especially under high-temperature and high-load conditions.
- Superior Oxidation and Thermal Stability: Resists breakdown and sludge formation, extending fluid life and maintaining performance over time.
- Broad Compatibility: Suitable for a wide range of older automatic transmissions and power steering systems, making it ideal for multi-vehicle servicing.
- Improved Component Protection: Offers excellent protection for copper and bronze components, helping to extend the life of transmission parts.
- Excellent Low-Temperature Fluidity: Ensures reliable operation and quick circulation in cold starts and harsh winter conditions.

Typical Characteristics:

Properties	Method	Unit	Value
Viscosity @ 40°C	ASTM D445	cSt	35.5
Viscosity @ 100°C	ASTM D445	cSt	7.3
Viscosity Index	ASTM D2770		177
Density @ 15°C	ASTM D4502	g/ml	0.85
Flash Point	ASTM D92	°C	195
Pour Point	ASTM D97	°C	-45

Package Sizes:

- 1000L
- 200L
- 20L

Meets the following specifications:

- **AISIN**
 - o JWS 3309 ATF, ATF-0T4
- **ALLISON**
 - o ALLISON
 - o ALLISON C2
 - o ALLISON C3
 - o ALLISON C4
- **ATF (Generic)**
 - o ATF 3100 PL085
 - o ATF 3403-M115
 - o ATF ETL-7045 E
 - o ATF K17
 - o ATF LA 2634
 - o ATF N402
 - o ATF SP-III
- **BMW**
 - o ATF4
 - o ETL-7045 / ETL-7045 E / ETL-8072B
 - o LA 2634
 - o LT 71141
 - o Multiple P/Ns (e.g., 81 22 9 400 272, 83 22 0 402 413, etc.)
- **BOSCH**
 - o BOSCH TE-ML 09
- **CITROËN / PEUGEOT**
 - o Z 000169756
- **DAIHATSU**
 - o D3-SP
- **FCA (Fiat Chrysler Automobiles)**
 - o ASRC, ATF+, ATF+2, ATF+3, ATF+4
 - o FIAT 9.55550-AV1 / AV4
 - o MB 236.10 / MB 236.12
 - o P/N 68333587AA
 - o SP-III, TYPE 7176E, TYPE 9602
- **FORD**
 - o ESP-M2C138-CJ / ESP-M2C166-H
 - o Multiple P/Ns (XT-2-QDX, XT-5-QM, etc.)
 - o SPEC WSS-M2C922-A1
- **GM (General Motors)**
 - o ATF Z1, DEX series (DEX-B, DEX-IIC, etc.)
 - o Multiple P/Ns (e.g., 19 40 700, 9985010)
 - o TYPE A SUFFIX A
 - o SATURN T-IV FLUID
- **HONDA / ACURA**
 - o ATF Z1 (P/N 08200-9001 / 08200-9001A)
- **HYUNDAI / KIA**
 - o ATF RED-1K, GENUINE ATF, JWS 3314
 - o SP, SP-II, SP-III
 - o Multiple P/Ns

- **ISUZU**
 - o ATF II / III
 - o GENUINE ATF
 - o P/N 08200-9001
- **JAGUAR**
 - o JLM 20238 / 20292 / 21044
 - o K17, JATCO 3100 PL085
 - o LT 71141
 - o WSS-M2C922-A1
- **JAMA**
 - o JASO M315, CLASS 1-A
- **LAND ROVER**
 - o ATF N402
 - o JWS3309US
- **MAN**
 - o 339A / 339D / 339F
- **MAZDA**
 - o ATF M-5, N-1, S-1, F-1, M3
 - o JWS3317
 - o TYPE T-IV, JWS 3309 ATF
- **MERCEDES**
 - o A 0019892203
 - o ATF 3403-M115
 - o SHEET 236.1 / 236.10 / 236.11 / 236.2 / 236.5 / 236.8
- **MINI**
 - o ATF JWS 3309 (P/N 83 22 0 402 413)
- **MITSUBISHI**
 - o ATF-J2, DIA QUEEN AW
 - o DII / DIII
 - o SP, SP-II, SP-III
- **NISSAN**
 - o FLUID A, MATIC D / J / K
 - o N402
- **PORSCHE**
 - o JWS 3309, LT 71141
 - o Multiple P/Ns (e.g., 000 043 204 41, 958 300 901 00)
- **PSA (Peugeot/Citroën)**
 - o AL4, 4HP20 (P/N 9730AE)
 - o B71 2340
- **RENAULT**
 - o DP-0, MATIC D2, SATF-D
- **ROLLS ROYCE**
 - o OIL NO. PL 31493PA
- **SAAB**
 - o ATF HP, JWS 3309
 - o P/N 93 160 393
- **SATURN**
 - o DEX-III
 - o T-IV FLUID (P/N 22689186)
- **SSANGYONG**
 - o DSIH 5M-52 / 5M-66
- **SUBARU**
 - o ATF HP (P/N K0140Y0700, SOA635040)
- **SUZUKI**
 - o ATF 2326 / 2384K / 3314 / 3317 / 5D06
 - o MATIC D / J
- **TOYOTA**
 - o JWS 3309, TYPE T-IV (P/N 08886-81015)
 - o TYPE D-II / T / T-II / T-III
- **VOLVO**
 - o P/N 1161521 / 1161621 / 1161640 / 1161540
 - o CE 97340 (AT100), CE 97341 (AT101)
- **VW / AUDI**
 - o G 052 162 / G 052 990 A2 / G 055 025
 - o G US 000 162
 - o LT 71141
- **ZF**
 - o LIFEFLUID 5 (ZF No. S671 090 170)
 - o TE-ML 05L / 11A / 11B / 21L