

# PRODUCT DATA SHEET

P: +61 8 6254 7777

Unit 2, 1110 Abernethy Road, High Wycombe, WA 6057

ABN: 64 384 013 844

# PX Total Drive Line 75W90

**PX Total Drive Line 75W90** is a fully synthetic PAO/Ester high-tech gear oil, enhanced with advanced additive technology for superior protection of gearboxes, transfer cases, and axles. This oil is engineered for demanding conditions and supports extended drain intervals, making it highly suitable for both passenger cars and commercial vehicles. Its versatility covers synchromesh transmissions, transfer cases, transaxles, and differentials that require API GL-5.

The exceptional properties of **PX Total Drive Line 75W90** help reduce operating temperatures, ensuring optimal performance even under extreme conditions. The oil's outstanding thermal stability and cleanliness contribute to the longevity and reliability of vehicle components, while its broad compatibility helps reduce product inventory and the risk of misapplication.

## Meets the following specifications:

- API GL5/MT-1
- MACK GO-J
- MAN 341 Type Z2/M3, 342 Type S1
- MB 235.8
- Meritor 0-76-N
- Scania STO 1:0, 2:0A FS
- Volvo: 97312
- ZF: TE-ML 02B, 05A, 12L, 12N 16F, 17B, 19C, 21A

#### **Advantages & Benefits:**

- Contains 100% PAO ester base oil designed for high performance.
- Smooth shifting lasts for the entire oil drain interval.
- Minimises the accumulation of detrimental deposits
- Excellent wear protection
- Provides protection against gear pitting
- Can extend transmission drain intervals











# **PRODUCT DATA SHEET**

P: +61 8 6254 777

Unit 2, 1110 Abernethy Road, High Wycombe, WA 6057

ABN: 64 384 013 844

## **Typical Characteristics:**

Properties	Method	Unit	Value
SAE Grade	SAE J 300		75W-90
Viscosity @ 40°C	ASTM D445	cSt	108
Viscosity @ 100°C	ASTM D445	cSt	15.5
Viscosity Index	ASTM D2770		152
Density @ 15°C	ASTM D4502	g/ml	0.87
Flash Point	ASTM D92	°C	205
Pour Point	ASTM D97	°C	-48

## **Package Sizes:**

- 1000L
- 200L
- 20L







