

PRODUCT DATA SHEET

P: +61 8 6254 7777

Unit 2, 1110 Abernethy Road, High Wycombe, WA 6057

ABN: 64 384 013 844

PX Transmatic CVT

PX Transmatic CVT is a fully synthetic Continuously Variable Transmission fluid formulated with premium synthetic base oils and a carefully engineered additive package. This includes friction modifiers, detergent-dispersants, oxidation inhibitors, viscosity index improvers, corrosion inhibitors, and defoaming agents. Designed as a versatile, multi-vehicle solution, it delivers dependable performance in a wide range of CVT-equipped passenger vehicles that utilize steel traction chains or belts.

PX Transmatic CVT offers excellent frictional control, thermal and oxidative stability, and superior anti-wear protection—ensuring smooth, consistent shifting and extended transmission life. Its outstanding shear stability maintains oil film strength under high stress, while its compatibility with a broad range of transmission seals makes it suitable for diverse vehicle applications. With enhanced power transfer efficiency and improved fuel economy, **PX Transmatic CVT** meets the demands of modern CVT systems increasingly adopted by global automakers.

Advantages & Benefits:

- Delivers smooth, seamless acceleration and operation
- Enhances metal-to-metal protection for prolonged CVT life
- Improves fuel efficiency by reducing internal friction
- Maintains consistent performance across a wide temperature range

Typical Characteristics:

Properties	Method	Unit	Value
Viscosity @ 40°C	ASTM D445	cSt	36
Viscosity @ 100°C	ASTM D445	cSt	7.2
Viscosity Index	ASTM D2770		169
Density @ 15°C	ASTM D4502	g/ml	0.85
Flash Point	ASTM D92	°C	190
Pour Point	ASTM D97	°C	-45











PRODUCT DATA SHEET

P: +61 8 6254 7777

Unit 2, 1110 Abernethy Road, High Wycombe, WA 6057

ABN: 64 384 013 844

Package Sizes:

- 1000L
- 200L
- 20L

Meets the following specifications:

- AUDI/ VW P/N G 052 180 (-A2)
- AUDI/ VW P/N G 052 516 A2
- BMW/ MINI/ PUNCH EZL 799
- BMW/ MINI/ PUNCH EZL 799A
- BMW P/N 83 22 0 136 376
- BMW P/N 83 22 0 429 154
- DAIHATSU AMMIX CVTF- DFE
- DAIHATSU AMMIX CVTF- DTC
- DODGE/ JEEP NS-2
- FCA CVTF+4 P/N 05191184AA
- FORD CFT23
- FORD CFT30
- FORD MERC C
- FORD WSS-M2C933-A, MOTORCRAFT P/N XT-7-QCFT
- GM CVTF I-GREEN2
- GM CVT P/N 19260800
- GM DEX-CVT
- HONDA CVTF P/N 08200-9006
- HONDA HMMF P/N 08260-99904 [WITHOUT STARTING CLUTCH]
- HONDA HCF-2 P/N 08200-HCF2
- MAZDA CVTF 3320
- MINI COOPER ZF CVT V1
- MITSUBISHI DIAMOND GREEN CVTF-J1
- MITSUBISHI DIAMOND GREEN CVTF-J4
- NISSAN NS-1
- NISSAN NS-2
- NISSAN NS-3
- RENAULT ELFMATIC
- SATURN P/N 22688912
- SHELL GREEN 1V
- SUBARU LINEARTRONIC CVTF
- SUBARU LINEARTRONIC CVTF-II; P/N K0425Y0711











PRODUCT DATA SHEET

P: +61 8 6254 7777

Unit 2, 1110 Abernethy Road, High Wycombe, WA 6057

ABN: 64 384 013 844

- SUBARU LINEARTRONIC CV-30 P/N K0425Y0710
- SUBARU e-CVTF
- SUBARU i-CVTF
- SUBARU HIGH TORQUE P/N K0421Y0700
- SUZUKI CVT FLUID GREEN 1
- SUZUKI CVT FLUID GREEN 2
- SUZUKI CVTF 3320
- SUZUKI NS-2
- TOYOTA / LEXUS FE
- TOYOTA / LEXUS TC







