

PX Transmatic LV

PX Transmatic LV is a premium, fully synthetic automatic transmission fluid designed to meet the rigorous demands of modern transmission systems. Engineered with advanced additive chemistry and smooth-shift technology, it delivers exceptional performance across a wide range of operating conditions. Its low viscosity formulation enhances fuel efficiency and ensures rapid circulation during cold starts, while maintaining robust protection against thermal breakdown at high temperatures. This makes it ideal for vehicles operating in both extreme climates and high-load environments.

PX Transmatic LV supports smooth, consistent gear shifts and extended transmission life by providing superior friction durability, oxidation resistance, and wear protection. It is suitable for use in most 6-, 7-, 8-, and 9-speed automatic transmissions found in Asian, European, and North American vehicles. The fluid meets or exceeds the latest global performance standards and is compatible with a broad spectrum of OEM specifications, offering excellent rust and corrosion protection and helping maintain transmission cleanliness over extended service intervals. Whether for daily driving or demanding conditions, **PX Transmatic LV** ensures reliable, long-lasting transmission performance.

Advantages & Benefits:

- PX Transmatic LV improves fuel economy through its low viscosity design, reducing internal friction.
- It resists thermal breakdown, ensuring stable performance under high temperatures.
- The fluid enables smooth, consistent gear shifts for a more comfortable drive.
- It protects against wear and sludge, extending transmission life.
- PX Transmatic LV is compatible with a wide range of global OEM specifications, making it highly versatile.

Typical Characteristics:

Properties	Method	Unit	Value
Viscosity @ 40°C	ASTM D445	cSt	29.7
Viscosity @ 100°C	ASTM D445	cSt	6.1
Viscosity Index	ASTM D2770		160
Density @ 15°C	ASTM D4502	g/ml	0.85
Flash Point	ASTM D92	°C	200
Pour Point	ASTM D97	°C	-45

Meets the following specifications:

Asian Manufacturers

- Toyota

- Type WS
- Type T-IV
- Type T-III
- Type T-II
- Type T
- Type D-II
- ATF FZ
- JWS 3309
- JWS 3324

- Nissan

- Matic S
- Matic J
- Matic K
- Matic D
- Matic W
- Matic R
- Fluid A

○ N402

- Honda / Acura

- ATF DW-1
- ATF Z1
- ATF Type 3.0
- ATF Type 3.1

- Hyundai / Kia

- SP-IV
- SP-III
- SP-II
- SPH-IV
- SPH-IV-RR
- Red-1K
- JWS 3314
- SP4-M1
- WS (NWS-9638)

- Mazda

- ATF FZ
- ATF M-5

- ATF N-1
- ATF S-1
- F-1
- JWS3317
- M3
- Type T-IV
- **Mitsubishi**
 - ATF-J2
 - ATF-J3
 - DIA QUEEN ATF-MA1
 - ATF-PA
 - AW
 - DII
 - DIII
 - SP
 - SP-II
 - SP-III
 - SP-IV
- **Subaru**
 - ATF HP
 - ATF-WS
- **Suzuki**
 - ATF 2326
 - ATF 2384K
 - ATF 3314
 - ATF 3317
- **Isuzu**
 - ATF 5D06
 - Matic D
 - Matic J
 - Matic S
- **Daihatsu**
 - ATF II
 - ATF III
 - ATF WSI
 - SCS
 - D3-SP
- **European Manufacturers**
 - **BMW / MINI**
 - ATF 3+
 - ATF 4
 - ATF 6
 - ETL-7045
 - ETL-8072B
 - LA 2634
 - LT 71141
 - M-L12108
 - JWS 3309
 - **Mercedes-Benz**
 - MB 236.1
 - MB 236.10
 - MB 236.11

- MB 236.12
- MB 236.14
- MB 236.15
- MB 236.2
- MB 236.41
- MB 236.5
- **Volkswagen / Audi**
 - G 052 162
 - G 052 533
 - G 052 990
 - G 055 005
 - G 055 025
 - G 055 162
 - G 055 540
 - G 060 162
 - LT 71141
- **Volvo**
 - 1161521
 - 1161621
 - 1161640
 - 1161540
 - 31 256 774
 - 31 256 775
- **Jaguar / Land Rover**
 - JLM 20238
 - JLM 20292
- JLM 21044
- LT 71141
- N402
- AW-1
- **Peugeot / Citroën / PSA**
 - AL4 / 4HP20
 - B71 2340
 - Z 000169756
- **Renault**
 - DP-0
 - MATIC D2
 - SATF-D
- **Maserati**
 - Oil No. 231603
- **Saab**
 - ATF HP
 - JWS 3309
- **Rolls Royce**
 - PL 31493PA
- **MAN**
 - 339A
 - 339D
 - 339F
- **ZF**
 - Lifeguardfluid 5
 - Lifeguardfluid 6

- Lifeguardfluid 8
- Lifeguardfluid 9
- TE-ML 11A
- TE-ML 11B

- XT-2-QDX
- XT-5-QM
- XT-6-QSP
- WSS-M2C922-A1

North American Manufacturers

- General Motors (GM)

- DEXRON-II
- DEXRON-III
- DEXRON-VI
- DEXRON HP
- Z1
- AW1
- Type A Suffix A

- Ford

- MERCON
- MERCON V
- MERCON LV
- XT-10-QLV

- Chrysler / FCA / Mopar

- ATF+
- ATF+2
- ATF+3
- ATF+4
- AW-1
- SP-III
- SP-IV
- Type 7176E
- Type 9602
- 8 & 9 Speed ATF

- Saturn

- T-IV Fluid
- DEX-IIIIG

Package Sizes:

- 1000L
- 200L
- 20L