

PX Turbo Multi Fleet 15W40

PX Turbo Multi Fleet 15W40 is a high-quality mineral diesel engine oil formulated with hydrocracked base oils and advanced additive technology to support long-term engine cleanliness and durability. Suitable for naturally aspirated, turbocharged, and supercharged engines, it performs well in both diesel and petrol vehicles including trucks, light commercials, SUVs, and older LPG-powered units.

This oil is ideal for mixed fleet operations and offers backward compatibility with legacy API specifications such as CH-4, CG-4, and CF-4, making it a versatile solution for older engines still in service. It is not recommended for engines fitted with Diesel Particulate Filters (DPFs) requiring low-mid SAPS oils. Always refer to the recommendation guide to ensure correct oil selection.

Meets the following specifications:

- SAE 15W40
- API CI-4 / SL
- ACEA A3/B4, E5/E7
- Allison C4
- CAT EFC-1-a, EFC-2
- CCMC-D4/PD2/G-4
- Cummins CES 20071 / 20072 / 20076 / 20077 / 20078
- DTC/MTU Type 2
- Detroit Diesel 93K215
- Global DHD-1
- JASO DH-1
- Mack EO-M PLUS, EO-N
- MAN 270, 271, M3275
- Mercedes-Benz 228.3/229.1
- RVI RLD-2
- Volvo VDS-3
- VW 505
- ZF TE-ML 07C

Advantages & Benefits:

- Provides superior engine protection through a Full Zinc Anti-Wear package that helps reduce wear under high-load and high-temperature conditions.
- Maintains engine cleanliness with a mid-ash formulation that effectively controls deposit build-up in the combustion chamber.
- Delivers consistent performance thanks to shear-stable viscosity modifiers that help the oil retain its thickness and protective qualities throughout its service life.
- Supports mixed fleet operations by being compatible with a wide range of diesel, petrol, and LPG engines, including older models still in use.

- Offers backward compatibility with legacy API specifications such as CH-4, CG-4, and CF-4, making it a reliable choice for servicing older engine technologies.

Typical Characteristics:

| Properties | Method | Unit | Value |
|-------------------|------------|----------|--------|
| SAE Grade | SAE J 300 | | 15W-40 |
| Viscosity @ 40°C | ASTM D445 | cSt | 112 |
| Viscosity @ 100°C | ASTM D445 | cSt | 15 |
| Viscosity Index | ASTM D2770 | | 139 |
| Density @ 15°C | ASTM D4502 | g/ml | 0.88 |
| Flash Point | ASTM D92 | °C | 220 |
| Pour Point | ASTM D97 | °C | -25 |
| TBN | ASTM D2896 | Mg KOH/g | 11 |

Package Sizes:

- 1000L
- 200L
- 20L