

## Slideway Oil 220

**Slideway Oil 220** is a premium lubricant specifically formulated for use in machine tool slideways, planers, lathes, and other machinery that require a tacky lubricant. This oil is made from high-quality paraffinic base oils and includes non-corrosive extreme pressure (EP) additives and a tackifier, which ensures excellent adhesion and anti-stick slip properties. These features help maintain smooth and precise movements of machine parts, reducing wear and tear.

**Slideway Oil 220** superior demulsibility allows it to effectively separate from water, preventing emulsions that can impair lubrication. Its oxidation stability ensures a longer service life by resisting chemical breakdown over time. Additionally, the oil provides robust protection against rust and foam development, which is crucial for maintaining the integrity and performance of heavily loaded machine tool slideways, whether they are horizontal or vertical.

### Meets the following specifications:

- Cincinnati P47
- ISO 220

### Typical Characteristics:

Properties	Method	Unit	Value
ISO Grade			220
Viscosity @ 40°C	ASTM D445	cSt	220
Viscosity @ 100°C	ASTM D445	cSt	19.1
Viscosity Index	ASTM D2770		97
Density @ 15°C	ASTM D4502	g/ml	0.89
Flash Point	ASTM D92	°C	250
Pour Point	ASTM D97	°C	-15

### Package Sizes:

- 1000L
- 200L
- 20L



**PHOENIX®**



**QP lubes**  
We stick to what's important



**SYNFORCE**