

ATF CVT 100

ATF CVT 100 is blended from high-performance synthetic base oils and carefully selected additives, including friction modifiers, detergent-dispersants, oxidation inhibitors, viscosity index improvers, corrosion inhibitors, and defoaming agents.

ATF CVT 100 is a new multi vehicle automatic transmission well-balanced fluid specially provided suitable performance in a wide-range of CVT-equipped passenger vehicles which transfer traction via steel-made traction chains or belts.

Meets the following specifications:

- AUDI/ VW P/N G 052 180 (-A2)
- AUDI/ VW P/N G 052 516 A2
- BMW/ MINI/ PUNCH EZL 799
- BMW/ MINI/ PUNCH EZL 799A
- BMW P/N 83 22 0 136 376
- BMW P/N 83 22 0 429 154
- DAIHATSU AMMIX CVTF- DFE
- DAIHATSU AMMIX CVTF- DTC
- DODGE/ JEEP NS-2
- FCA CVTF+4 P/N 05191184AA
- FORD CFT23
- FORD CFT30
- FORD MERC C
- FORD WSS-M2C933-A, MOTORCRAFT P/N XT-7-QCFT
- GM CVTF I-GREEN2
- GM CVT P/N 19260800
- GM DEX-CVT
- HONDA CVTF P/N 08200-9006 HONDA HMMF P/N 08260-99904 [WITHOUT STARTING CLUTCH]
- HONDA HCF-2 P/N 08200-HCF2
- MAZDA CVTF 3320
- MINI COOPER ZF CVT V1
- MITSUBISHI DIAMOND GREEN CVTF-J1
- MITSUBISHI DIAMOND GREEN CVTF-J4
- NISSAN NS-1
- NISSAN NS-2



PHOENIX®



We stick to what's important



SYNFORCE

- NISSAN NS-3
- RENAULT ELFMATIC
- SATURN P/N 22688912
- SHELL GREEN 1V
- SUBARU LINEARTRONIC CVTF
- SUBARU LINEARTRONIC CVTF-II; P/N K0425Y0711
- SUBARU LINEARTRONIC CV-30 P/N K0425Y0710
- SUBARU e-CVTF
- SUBARU i-CVTF
- SUBARU HIGH TORQUE P/N K0421Y0700
- SUZUKI CVT FLUID GREEN 1
- SUZUKI CVT FLUID GREEN 2
- SUZUKI CVTF 3320
- SUZUKI NS-2
- TOYOTA / LEXUS FETOYOTA / LEXUS TC

Typical Characteristics:

Properties	Method	Unit	Value
Viscosity @ 40°C	ASTM D445	cSt	36
Viscosity @ 100°C	ASTM D445	cSt	7.2
Viscosity Index	ASTM D2770		169
Density @ 15°C	ASTM D4502	g/ml	0.85
Flash Point	ASTM D92	°C	190
Pour Point	ASTM D97	°C	-45

Package Sizes:

- 1000L
- 200L
- 20L
- 5L