

## **Bluesol**

**Bluesol** is a high-purity diesel exhaust fluid designed for use in modern diesel engines equipped with selective catalytic reduction systems. It plays a critical role in reducing exhaust emissions, supporting cleaner operation and helping vehicles meet stringent environmental requirements.

Manufactured using high-quality urea and demineralised water, **Bluesol** is formulated to ensure consistent performance and protect sensitive SCR system components. When injected into the exhaust system, it helps convert harmful nitrogen oxide emissions into harmless nitrogen and water vapour, supporting efficient emissions control without impacting engine performance. Its stable and contaminant-free formulation helps prevent blockages, deposits, and system faults, ensuring reliable operation across a wide range of commercial and fleet applications.

### **Meets the following specifications:**

- DIN 70070
- AUS 32
- ISO 22241
- Manufactured with ISO 9001:2008

### **Advantages & Benefits:**

- Reduces harmful exhaust emissions for cleaner operation
- Supports efficient performance of SCR systems
- Helps prevent deposits and blockages in dosing systems
- Manufactured to high purity standards for consistent quality
- Maintains reliability of emissions control systems
- Suitable for modern diesel engines requiring AdBlue/DEF



## Typical Characteristics:

Properties	Unit	Value
Urea Content	wt%	32.5
Viscosity @ 25°C	cSt	1.4
Refracting Index @ 20°C	cSt	1.38
Density @ 20°C	g/ml	1.09

## Package Sizes:

- 1000L
- 210L
- 20L

