

Diesel Max 15W40

Diesel Max 15W40 is a high-performance heavy-duty diesel engine oil designed to deliver reliable protection and consistent performance across a wide range of diesel engines and operating conditions. It is well suited to mixed fleet environments, providing dependable lubrication for both modern and older engines used in on-road and off-road applications.

Formulated with a robust base oil system and advanced additive technology, **Diesel Max 15W40** provides strong protection against wear, soot-related thickening, and deposit formation while maintaining stable viscosity under high temperature and load. It helps support extended service intervals by controlling oxidation and neutralising acids generated during combustion, ensuring long-term engine cleanliness and durability. Designed for high-utilisation environments such as transport, construction, and agriculture, it delivers consistent performance and protection where reliability and uptime are essential.

Meets the following specifications:

- ACEA E11 / E9 / E7
- API CK-4 / CJ-4 / SN
- ALLISON TES 439
- CAT ECF-3
- Cummins CES 20086
- Deutz DQC III-18 LA / III-10 LA
- Detroit Diesel 93K223
- JASO DH-2
- Mack EO-S-4.5
- MAN M3775
- MB 228.31 / DTFR 15C100
- MTU Type 2.1
- Renault RLD-3
- SAE 15W-40
- Volvo VDS-4.5

Advantages & Benefits:

- Supports extended oil drain intervals for improved fleet efficiency
- Provides strong protection under high load and high temperature operation
- Maintains viscosity stability and resists breakdown over time
- Helps control oxidation, acid formation, and deposit build-up
- Suitable for modern diesel engines with advanced emissions systems
- Delivers reliable performance across mixed fleet and heavy-duty applications



PHOENIX®



We stick to what's important



SYNFORCE

Typical Characteristics:

Properties	Method	Unit	Value
SAE Grade	SAE J 300		15W-40
Viscosity @ 40°C	ASTM D445	cSt	110
Viscosity @ 100°C	ASTM D445	cSt	15
Viscosity Index	ASTM D2770		142
Density @ 15°C	ASTM D4502	g/ml	0.875
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-39
TBN	ASTM D2896	Mg KOH/g	9.9

Package Sizes:

- 1000L
- 200L
- 20L
- 10L
- 5L