

Eco Advance 0W20

Eco Advance 0W20 is a fully synthetic passenger car motor oil formulated with the latest mid SAPS (Sulphated Ash, Phosphorus, and Sulphur) additive technology. **Eco Advance 0W20** prevents oil oxidation, keeps engines clean, and minimizes wear, making it ideal for modern engines that run hotter due to advanced engineering features like turbocharging and variable timing.

This oil is suitable for use in modern multi-cam, multi-valve engines, including naturally aspirated, supercharged, and turbocharged low emission petrol engines.

Meets the following specifications:

- ACEA C5 / C6
- API SP
- ILSAC GF-6A
- MB 229.71 / 229.72
- Volvo VVC RBS0-2AE
- Opel OV 040 1547 - A20
- JLR STJLR 03-5006-16
- Ford WSS-M2C947-B1 / WSS-M2C962-A1
- Fiat 9.55535-GSX
- Chrysler MS-12145

Typical Characteristics:

Properties	Method	Unit	Value
SAE Grade	SAE J 300		0W-20
Viscosity @ 40°C	ASTM D445	cSt	44
Viscosity @ 100°C	ASTM D445	cSt	8.3
Viscosity Index	ASTM D2770		165
Density @ 15°C	ASTM D4502	g/ml	0.84
Flash Point	ASTM D92	°C	215
Pour Point	ASTM D97	°C	-42
TBN	ASTM D2896	Mg KOH/g	8.7



PHOENIX®



Package Sizes:

- 1000L
- 200L
- 20L
- 5L



PHOENIX®



We stick to what's important



SYNFORCE