

Eco Power 5W40

Eco Power 5W40 is a premium quality, fully synthetic motor oil designed for hybrid and downsized engines. This Mid SAPS lubricant is compatible with the latest generation aftertreatment systems and meets the latest API SN/CF and OEM performance standards. It effectively disperses water and fuel, preventing increased bearing wear, sludge formation, and potential engine damage in hybrid vehicles.

Meets the following specifications:

- API SN/CF
- ACEA C3
- GM Proprietary Fill - Diesel
- BMW Long Life-04
- Mercedes-Benz 226.5, 229.31, 229.51
- MB-Approval 229.51
- Porsche A40
- VW 502 00/ 505 01
- Renault RN0700/ RN0710

Typical Characteristics:

Properties	Method	Unit	Value
SAE Grade	SAE J 300		5W-40
Viscosity @ 40°C	ASTM D445	cSt	88
Viscosity @ 100°C	ASTM D445	cSt	14.9
Viscosity Index	ASTM D2770		176
Density @ 15°C	ASTM D4502	g/ml	0.85
Flash Point	ASTM D92	°C	215
Pour Point	ASTM D97	°C	-40
TBN	ASTM D2896	Mg KOH/g	7.4

Package Sizes:

- 1000L
- 200L
- 20L
- 5L



PHOENIX®



SYNFORCE